



Made in Denmark!
Importer: Ltd "Abschliff Latvija"
Riga, A Čaka iela 107 K2
Phone: +371 67843844, 67843845
Fakss: +371 67272792
Mob.: +371 26177888
E-mail: info@abschliff.lv
www.abschliff.lv

<https://www.facebook.com/Abschliff-Latvija-100679528475676/>



Open: Monday to Friday – 9⁰⁰-18⁰⁰, Saturday- 10⁰⁰-14⁰⁰, Sunday – closed

WOCA Natural Soap - for clean and maintain

Description: clean and maintain oiled, waxed and soaped wood surfaces with Natural Soap. This mild, penetrating soap removes dirt and helps prevent the wood from drying out and cracking. It leaves behind a microscopic, breathable soap layer on the surface that maximizes resistance and makes the surface easier to keep clean. Natural Soap is indoor climate labelled and free of perfume and additives.

- Nourishing effect
- For the basic treatment of softwood
- Ideal for floors, furniture, table tops and panels
- For regularly cleaning

Declaration: 15% or over but less than 30% Soap. The following applies only for colours, less than 5%: colouring agents.

pH-value: 10

Color: white, colorless.

Application area: WOCA Natural Soap is suitable for regular cleaning and maintenance of oiled, waxed and soaped wood surfaces. The soap is especially ideal for floors, furniture, table tops and panels.

Surface preparation: Daily cleaning is made with vacuum cleaner or broom. The frequency of floor cleaning depends on the wear on the floor. Very dirty floors may be cleaned with WOCA Intensive Wood Cleaner before using Natural Soap.

! Always remember to test on a less visible spot to check the compatibility of the surface with the product.

Work instructions:

- 1) Natural Soap is shaken carefully before use. Make sure the pigments are mixed well.
- 2) 125 ml Natural Soap is mixed into 5 L of cold water. Wipe down the surface with a well-wrung mop.
For best results, use two buckets: one with soap water and the second with clean water to rinse the dirty mop.
- 3) Clean the floor with minimum quantity of water – leave soap water on floor briefly in order to dissolve dirt.
- 4) Remove dirty soap water with hard-wrung mop or cloth and rinse out in bucket with clean water.

! Always wipe down the surface with soap water and a hard-wrung mop or cloth in order to re-establish the protective soap film.

Application temperature: +15-30°C

Consumption: approx., 320 - 400 m²/l depending on wood type and surface.

Packaging: 1l, 2,5l

Storage: under cool and dry conditions. Close lid tightly when not in use. Shelf-life of unopened container 36 months +10-25°C. Keep out of reach of children. Do not expose to heat (e.g. sunlight). Store frost-free during winter and cool during summer.

