# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 14.05.2019

Revision: 14.05.2019

SECTIO	DN 1: Identification of the substance/mixture and of the company/undertaki	ing
· 1.1 Prod	luct identifier	
· Trade na	ame <u>NATURAL STONE FLOOR RESIN PU 1K</u>	
· 1.2 Relev	number: 11731/5 want identified uses of the substance or mixture and uses advised against er relevant information available.	
· Applicat	tion of the substance / the mixture Binder	
• <b>Manufac</b> MUREXII Franz v. I A-2700 V	nils of the supplier of the safety data sheet cturer/Supplier: IN GmbH Furtenbachstr. 1 Wiener Neustadt 8 (0)2622/27401	
· 1.4 Emer	<b>ng department:</b> r.wachlhofer@murexin.com F <b>gency telephone number:</b> Ional poisons Emergency number.: +44 (0) 870 600 6266	
SECTIO	ON 2: Hazards identification	
	sification of the substance or mixture cation according to Regulation (EC) No 1272/2008	
	GHS07	
Acute To	ox. 4 H332 Harmful if inhaled.	
Skin Sen	, .	
STOT SE	E 3 H335 May cause respiratory irritation.	
Aquatic C	Chronic 3 H412 Harmful to aquatic life with long lasting effects.	
· <b>Labelling</b> The prod	el elements og according to Regulation (EC) No 1272/2008 duct is classified and labelled according to the CLP regulation. pictograms	
GHS07		
Cirra e Luc		
• <b>Hazard-c</b> Hexamet Bis(1,2,2, methyl 1,	<i>vord</i> Warning <i>determining components of labelling:</i> thylen-1,6-diisocyanat homopolymer 2,6,6-pentamethyl-4-piperidyl)sebacat ,2,2,6,6-pentamethyl-4-piperidylsebacate	
	statements armful if inhaled.	
H317 Ma	ay cause an allergic skin reaction.	
	ay cause respiratory irritation. armful to aquatic life with long lasting effects.	
	ionary statements	
P101	If medical advice is needed, have product container or label at hand.	
P102	Keep out of reach of children.	
P103 P261	Read label before use. Avoid breathing mist/vapours/spray.	
P273	Avoid release to the environment.	
	(Contd. on pag	e 2)

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 14.05.2019

Version number 5

Revision: 14.05.2019

# Trade name NATURAL STONE FLOOR RESIN PU 1K

(Contd. of page 1)

P280 Wear protective gloves / eye protection.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards

# · Results of PBT and vPvB assessment

• PBT: Not applicable.

· vPvB: Not applicable.

### SECTION 3: Composition/information on ingredients

#### - 3.2 Chemical characterisation: Mixtures

· **Description:** Mixture consisting of the following components with harmless additives.

<ul> <li>Dangerous components:</li> </ul>		
CAS: 28182-81-2	Hexamethylen-1,6-diisocyanat homopolymer	50-100%
NLP: 500-060-2	1 Acute Tox. 4, H332; Skin Sens. 1, H317; STOT	
Reg.nr.: 01-2119488934-20-0000		
01-2119485796-17-000X		
CAS: 41556-26-7	Bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacat	1-2.5%
	Aquatic Acute 1, H400; Aquatic Chronic 1, H410 Skin Sens. 1, H317	
CAS: 82919-37-7	methyl 1,2,2,6,6-pentamethyl-4-piperidylsebacate	<0.5%
	Aquatic Acute 1, H400; Aquatic Chronic 1, H410 Skin Sens. 1, H317	

#### SECTION 4: First aid measures

4.1 Description of first aid measures

- · General information Instantly remove any clothing soiled by the product.
- · After inhalation

Supply fresh air and call for doctor for safety reasons.

In case of unconsciousness bring patient into stable side position for transport.

· After skin contact

Instantly wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eye contact Rinse opened eye for several minutes under running water.

· After swallowing Do not induce vomiting; instantly call for medical help.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

• 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

# SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· Suitable extinguishing agents

CO2, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam. • For safety reasons unsuitable extinguishing agents Water with a full water jet.

- 5.2 Special hazards arising from the substance or mixture

Carbon monoxide (CO)

Nitrogen oxides (NOx)

Can be released in case of fire

(Contd. on page 3)

GB

Printing date 14.05.2019

Version number 5

Revision: 14.05.2019

#### Trade name NATURAL STONE FLOOR RESIN PU 1K

(Contd. of page 2)

(Traces) Hydrogen cyanide (HCN)

- 5.3 Advice for firefighters
- Protective equipment:
- Do not inhale explosion gases or combustion gases.
- Wear self-contained breathing apparatus.
- · Additional information Collect contaminated fire fighting water separately. It must not enter drains.

# SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective clothing. Keep away from ignition sources Ensure adequate ventilation
  6.2 Environmental precautions: Do not allow product to reach sewage system or water bodies. Do not allow to enter the ground/soil. Inform respective authorities in case product reaches water or sewage system.
  6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose of contaminated material as waste according to item 13. Allow to solidify. Collect mechanically.
  6.4 Reference to other sections See Section 7 for information on safe handling
  - See Section 8 for information on personal protection equipment. See Section 13 for information on disposal.

# SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Keep containers tightly sealed.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about protection against explosions and fires: No special measures required.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage
- · Requirements to be met by storerooms and containers: Store only in the original container.
- · Information about storage in one common storage facility: Store away from foodstuffs.

· Further information about storage conditions:

Store in cool, dry conditions in well sealed containers.

• 7.3 Specific end use(s) No further relevant information available.

# SECTION 8: Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

· 8.1 Control parameters

Components with critical values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

• Additional information: The lists that were valid during the compilation were used as basis.

- · 8.2 Exposure controls
- · Personal protective equipment
- · General protective and hygienic measures

The usual precautionary measures should be adhered to in handling the chemicals.

(Contd. on page 4)

GB

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 14.05.2019

Version number 5

Revision: 14.05.2019

# Trade name NATURAL STONE FLOOR RESIN PU 1K

(Contd. of page 3)

Keep away from foodstuffs, beverages and food. Instantly remove any soiled and impregnated garments. Wash hands during breaks and at the end of the work.

· Breathing equipment:

Use breathing protection in case of insufficient ventilation. Filter A/P2.

· Protection of hands: Protective gloves.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

- Penetration time of glove material
- The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
- · Eye protection: Safety glasses
- · Body protection: Protective work clothing.

# SECTION 9: Physical and chemical properties

9.1 Information on basic physical and c	hemical properties	
General Information Appearance:		
Form:	Fluid	
Colour:	Colourless	
· Smell:	Characteristic	
· Odour threshold:	Not determined.	
· pH-value:	Not determined.	
· Change in condition		
Melting point/freezing point:	Not determined	
Initial boiling point and boiling range:	175 °C	
· Flash point:	65 °C	
· Inflammability (solid, gaseous)	Not applicable.	
· Ignition temperature:	445 °C	
· Decomposition temperature:	Not determined.	
· Self-inflammability:	Product is not selfigniting.	
· Explosive properties:	Product is not explosive.	
· Critical values for explosion:		
Lower:	Not determined.	
Upper:	Not determined.	
· Steam pressure at 20 °C:	>0 hPa	
· Density at 20 °C	1.2 g/cm <sup>3</sup>	
· Relative density	Not determined.	
· Vapour density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
Water:	immiscible	
· Partition coefficient: n-octanol/water:	Not determined.	
· Viscosity:		
dynamic:	Not determined.	
		(Contd. on page

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 14.05.2019

Version number 5

Revision: 14.05.2019

#### Trade name NATURAL STONE FLOOR RESIN PU 1K

		(Contd. of page 4
kinematic:	Not determined.	
· Solvent content:		
Solids content:	0.0 %	
· 9.2 Other information	No further relevant information available.	

# SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Conditions to be avoided: No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** Exothermic reaction Reacts with alcohols Reacts with amines
- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: None

# SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity
- Harmful if inhaled.

# · LD/LC50 values that are relevant for classification:

28182-81-2 Hexamethylen-1,6-diisocyanat homopolymer

Oral	LD50	>2,500 mg/kg (rat)
	LD50	>2,000 mg/kg (rat)
Inhalative	LC50/4 h	0.39 mg/l (rat)

#### Primary irritant effect:

- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure

May cause respiratory irritation.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

# SECTION 12: Ecological information

· 12.1 Toxicity

•	Aqu	atic	tox	icity.
---	-----	------	-----	--------

28182-81-2 Hexamethylen-1,6-diisocyanat homopolymer

EC 50 >100 mg/l (Daphnia magna (Großer Wasserfloh))

LC50 >100 mg/l (Brachydanio rerio (Zebrabärbling))

- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.

· 12.4 Mobility in soil No further relevant information available.

(Contd. on page 6)

GB

Printing date 14.05.2019

Version number 5

Revision: 14.05.2019

#### Trade name NATURAL STONE FLOOR RESIN PU 1K

(Contd. of page 5)

- Ecotoxical effects:
- Remark: Harmful to fish
   Additional ecological information:
- · General notes:
- Harmful to aquatic organisms
- Water hazard class (Germany) 1 (Self-assessment): slightly hazardous for water.

Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.

- 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

# SECTION 13: Disposal considerations

# · 13.1 Waste treatment methods

· Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

#### · European waste catalogue

08 04 09<sup>\*</sup> waste adhesives and sealants containing organic solvents or other hazardous substances

### · Uncleaned packagings:

• **Recommendation:** Disposal must be made according to official regulations.

14.1 UN-Number		
ADR, ADN, IMDG, IATA	Void	
14.2 UN proper shipping name	Vaid	
ADR, ADN, IMDG, IATA	Void	
14.3 Transport hazard class(es)		
ADR, ADN, IMDG, IATA		
Class	Void	
14.4 Packing group		
ADR, IMDG, IATA	Void	
14.5 Environmental hazards:		
Marine pollutant:	No	
14.6 Special precautions for user	Not applicable.	
14.7 Transport in bulk according to An	nex II	
of Marpol and the IBC Code	Not applicable.	

(Contd. on page 7)

GP

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 14.05.2019

Version number 5

Revision: 14.05.2019

#### Trade name NATURAL STONE FLOOR RESIN PU 1K

(Contd. of page 6)

### SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases H317 May cause an allergic skin reaction. H332 Harmful if inhaled. H335 May cause respiratory irritation. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. · Contact: Hr. Ing. Wachlhofer (+43 02622/27401 161) Abbreviations and acronyms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Acute Tox. 4: Acute toxicity - Category 4 Skin Sens. 1: Skin sensitisation - Category 1 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3 \* \* Data compared to the previous version altered.